

## Pressure Relief Valve (PRV)

## **Model Selection Chart**

NPT (Male) x NPT (Female)					
Sr. No.	Inlet Thread Type NPT Male	Outlet Thread type NPT Female	<b>Model No.</b> For MOC: <b>SS316</b>		
1	1/4"	1/4"	SS-PRV-4M-4F		
2	3/8"	3/8"	SS-PRV-6M-6F		
3	1/2"	1/2"	SS-PRV-8M-8F		

NPT (Male) x Tube OD					
Sr. No.	Inlet Thread Type NPT Male	Outlet Tube OD Size: Inch/MM	<b>Model No.</b> For MOC: <b>SS316</b>		
1	1/4"	1/4"	SS-PRV-4M-4		
2	1/4"	6mm	SS-PRV-4M-6mm		
3	1/2"	1/2"	SS-PRV-8M-8		
4	1/2"	12mm	SS-PRV-8M-12mm		



Material Grade Selection Chart				
For following Material Grade (MOC)	Replace First Two Letters of Model No. with following			
SS316L	SSL			
SS304	S4			
SS304L	S4L			
Brass	В			
Alloy 400	ML			
Alloy 600	INC			
Alloy C276	HC			
Carbon Steel	CS			
Note: Above Model Nos, are for NPT Threads, For BSP Threads Add -B & for BSPT Threads add -BT at end of Model Nos,				

**Head Office** 

"TRUEWAY HOUSE", Plot No. 535/14-15, Sonawala Cross Road No. 2, Nr. M.K. Industrial Estate, Goregaon (East) Mumbai - 400 063, INDIA. Mobile: +91 9321756212, +91 9004146034 | Phone: +91 22 26852241, 26851052.

www.truewayindia.in

